

# Avstrykare



## TEMPERATURRESISTENS (°C)

PU (U500)	-30 till 125
NBR	-25 till 100
POM	-50 till 100*
PU-D57	-30 till 125
PTFE	-200 till 260

\*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	WR01	PU, NBR	-	4
	WR01A	PU, NBR	-	4
	WR01	PU, NBR	-	4
	WR02A	PU, NBR	-	4
	WR02B	PU, NBR	-	4
	WR02C	PU, NBR	-	4
	WR02D	PU, PU-D57	-	4
	WR03	PU/POM, NBR/POM	-	4
	WR04	PU, NBR	-	4
	WR07	POM, PA, PU-D57	-	1
	WR08	POM, PA, PU-D57	-	1
	WR11	PU, NBR	-	4
	WR12	PU, NBR	-	4
	WR13	PTFE/NBR	15	10
	WR13_E2	PTFE/NBR	15	10
	WR14	PTFE/NBR	15	10
	WR15	PTFE/NBR	15	10
	WR16	PTFE/NBR	16	10
	WR17	PU, NBR	-	4
	WR18	PU, NBR	-	4

