

# Avstrykare



## TEMPERATURRESISTENS (°C)

PU (U500)	-30 till 125
NBR	-25 till 100
POM	-50 till 100*
PU-D57	-30 till 125
PTFE	-200 till 260

\*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	WR01	PU, NBR	-	4
	WR01A	PU, NBR	-	4
	WR01	PU, NBR	-	4
	WR02A	PU, NBR	-	4
	WR02B	PU, NBR	-	4
	WR02C	PU, NBR	-	4
	WR02D	PU, PU-D57	-	4
	WR03	PU/POM, NBR/POM	-	4
	WR04	PU, NBR	-	4
	WR07	POM, PA, PU-D57	-	1
	WR08	POM, PA, PU-D57	-	1
	WR11	PU, NBR	-	4
	WR12	PU, NBR	-	4
	WR13	PTFE/NBR	15	10
	WR13_E2	PTFE/NBR	15	10
	WR14	PTFE/NBR	15	10
	WR15	PTFE/NBR	15	10
	WR16	PTFE/NBR	16	10
	WR17	PU, NBR	-	4
	WR18	PU, NBR	-	4























# Stångtätningar



## TEMPERATURRESISTENS (°C)

PU (U500)	-30 till 125
NBR	-25 till 100
POM	-50 till 100*
PU-D57	-30 till 125
PTFE	-200 till 260

\*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	RS01	PU, NBR, FPM	400/160/160	0,5
	RS01A	PU, NBR, FPM	300/160/160	0,5
	RS01B	PU, NBR, FPM	400/160/160	0,5
	RS01C	NBR, FPM	160/160	1
	RS02	PU/POM, NBR/POM, FPM/PTFE	700/250/250	0,5
	RS02A	PU/POM, NBR/POM, FPM/PTFE	700/250/250	0,5
	RS02B	PU/PTFE	700	0,5
	RS02C	PU/POM	400	5
	RS03	PU/NBR	400	0,5
	RS04	PU/NMB/POM	700	0,5
	RS04A	PU/NBR/POM	700	0,5
	RS05	PU, NBR	25	1
	RS05A	PU, NBR	25	1
	RS08	PU, NBR	400/160	0,3
	RS09	PU-D57/NBR, PTFE/NBR	600/400	5/10
	RS09A	PU-D57/NBR, PTFE/NBR	600/400	5/10
	RS09B	PU-D57/NBR, PTFE/NBR	600/400	5/10
	RS10-12B	PU/POM, NBR/POM	500/250	0,7
	RS91	PU-D57/NBR, PTFE/NBR	600/400	5/10
	RS91B	PU-D57/NBR, PTFE/NBR	600/400	5/10




# Stångtätningar



## TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

\*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	RS17	PU, NBR	400/160	0,5
	RS17A	PU/POM	700	0,5
	RS17B	PU/NBR	400	0,5
	RS17C	PU/NBR/POM	700	1
	RS17D	PU, NBR	400/160	0,5
	RS17E	PU/POM	700	0,5
	RS19	PTFE-virgin/V-spring PTFE-filled/V-spring	200 400	0,5
	RS19A	PTFE/V-spring	150	5
	RS20	NBR/POM	700	0,5
	RS31-33	PU/POM	500	0,5
	RS35	PU	400	0,5
	RS35A	PU	400	1























# Kolvätningar



## TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

\*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	PS01	PU, NBR, FPM	400/160/160	0,5
	PS01A	PU, NBR, FPM	300/160/160	0,5
	PS01B	PU, NBR, FPM	400/160/160	0,5
	PS01C	NBR, FPM	160/160	1
	PS02	PU/POM, NBR/POM, FPM/PTFE	700/250/250	0,5
	PS02A	PU/POM, NBR/POM, FPM/PTFE	700/250/250	0,5
	PS03	PU/NBR	400	0,5
	PS04	PU/NBR/POM	700	0,5
	PS04A	PU/NBR/POM	700	0,5
	PS05	PU, NBR	25	1
	PS05A	PU, NBR	25	1
	PS08	PU-D57/NBR, PTFE/NBR	600/400	5/15
	PS08A	PU/NBR, PU-D57/NBR, PTFE/NBR	250/400/400	1/5/15
	PS08B	PU-D57/NBR, PTFE/NBR	600/400	5/10
	PS08C	PTFE/NBR	400	2
	PS08D	PTFE/NBR	400	3
	PS08E	PU-D57/NBR, PTFE/NBR	600/400	5/10
	PS08F	PU-D57/NBR, PTFE/NBR	400/250	5/1
	PS81	PU-D57/NBR, PTFE/NBR	600/400	5/10
	PS81B	PU-D57/NBR, PTFE/NBR	600/400	5/10






# Kolvätningar

## TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

\*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	PS81C	PU/NBR, PU-D57/NBR, PTFE/NBR	250/400/400	1/5/15
	PS09	PU, NBR, POM	400	0,5
	PS09A	PTFE/NBR/POM	400	1
	PS10-12B	PU/POM, NBR/POM	500/250	0,7
	PS16	PU, NBR	160	0,5
	PS16A	PU, NBR	160	0,5
	PS17	PU/POM, NBR/POM	400/250	0,5
	PS17A	PU/POM, NBR/POM	400/250	0,5
	PS17B	PU/POM, NBR/POM	400/250	0,5
	PS19	PTFE-virgin/V-spring PTFE-filled/V-spring	200/400	15
	PS19A	PTFE-virgin/V-spring PTFE-filled/V-spring	200/400	2
	PS20	NBR/POM	700	0,5
	PS23	PU/NBR/POM	400	0,5
	PS35	PU	400	0,4
	PS35A	PU	400	0,4



# Symmetriska Tätningar



## TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

\*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	PRS06	PU, NBR	400/160	0,5
	PRS06A	PU, NBR	300/160	0,5
	PRS06B	PU, NBR	400/160	0,5
	PRS06C	PU, NBR	400/160	0,3
	PRS06D	PU, NBR	400/160	0,5
	PRS06E	PU, NBR	400/160	0,5
	PRS07	PU/NBR	400	0,5
	PRS10SP	PU, FPM, POM	-	-
	PRS10-12	PU/POM, NBR/POM	500/250	0,5
	PRS10-12A	PU/POM, NBR/POM	500/250	0,7
	PRS13-15	PU/POM, NBR/POM	500/250	0,5
	PRS18	PU/NBR	400	0,5
	PRS19	PTFE-virgin/V-spring PTFE-filled/V-spring	200/400	15
	PRS19B	PTFE-virgin/Helicoil spring PTFE-filled/Helicoil spring	200/400	5
	PRS19C	PTFE-virgin/Helicoil spring PTFE-filled/Helicoil spring	200/400	5
	PRS19D	PTFE-virgin/Helicoil spring PTFE-filled/Helicoil spring	200/400	5
	PRS22	PU/POM, NBR/POM, FPM/PTFE	400/160/160	0,5
	PRS25-27	PTFE-virgin PTFE-filled	100	1,5
	PRS99	PU, NBR, FPM	400/160/160	0,5



# Svivelätningar

## TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

\*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	R08	PTFE/NBR	350	0,4
	R08D	PTFE/NBR	350	0,4
	R09	PTFE/NBR	350	0,4
	R09A	PTFE/NBR	350	0,4
	R10	PTFE/NBR	350	0,4
	R10A	PTFE/NBR	350	0,4
	R11	PTFE/NBR	350	0,4
	R11D	PTFE/NBR	350	0,4








# Back-up ringar



## TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

\*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	BUR08	POM, PTFE	-	-
	BUR09	POM, PTFE	-	-
	BUR10	POM, PTFE	-	-
	BUR11	POM, PTFE	-	-
	BUR12	POM, PTFE	-	-
	BUR13	POM, PTFE	-	-













# Stödringar



## TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

\*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	BWR01	POM, PTFE, Polyester-fabric	-	4
	BWR01A	POM, PTFE	-	4
	BWR03	POM, PTFE	-	4
	BWR04	POM, PTFE	-	4
	BWR05	POM, PTFE	-	4
	BWR06	POM, PTFE	-	4
	BWR07	POM, PTFE	-	4
	BWR08	POM, PTFE	-	4
	BWR09	-	-	-

