





















Kolvätningar



TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	PS01	PU, NBR, FPM	400/160/160	0,5
	PS01A	PU, NBR, FPM	300/160/160	0,5
	PS01B	PU, NBR, FPM	400/160/160	0,5
	PS01C	NBR, FPM	160/160	1
	PS02	PU/POM, NBR/POM, FPM/PTFE	700/250/250	0,5
	PS02A	PU/POM, NBR/POM, FPM/PTFE	700/250/250	0,5
	PS03	PU/NBR	400	0,5
	PS04	PU/NBR/POM	700	0,5
	PS04A	PU/NBR/POM	700	0,5
	PS05	PU, NBR	25	1
	PS05A	PU, NBR	25	1
	PS08	PU-D57/NBR, PTFE/NBR	600/400	5/15
	PS08A	PU/NBR, PU-D57/NBR, PTFE/NBR	250/400/400	1/5/15
	PS08B	PU-D57/NBR, PTFE/NBR	600/400	5/10
	PS08C	PTFE/NBR	400	2
	PS08D	PTFE/NBR	400	3
	PS08E	PU-D57/NBR, PTFE/NBR	600/400	5/10
	PS08F	PU-D57/NBR, PTFE/NBR	400/250	5/1
	PS81	PU-D57/NBR, PTFE/NBR	600/400	5/10
	PS81B	PU-D57/NBR, PTFE/NBR	600/400	5/10


















Kolvätningar

TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	PS81C	PU/NBR, PU-D57/NBR, PTFE/NBR	250/400/400	1/5/15
	PS09	PU, NBR, POM	400	0,5
	PS09A	PTFE/NBR/POM	400	1
	PS10-12B	PU/POM, NBR/POM	500/250	0,7
	PS16	PU, NBR	160	0,5
	PS16A	PU, NBR	160	0,5
	PS17	PU/POM, NBR/POM	400/250	0,5
	PS17A	PU/POM, NBR/POM	400/250	0,5
	PS17B	PU/POM, NBR/POM	400/250	0,5
	PS19	PTFE-virgin/V-spring PTFE-filled/V-spring	200/400	15
	PS19A	PTFE-virgin/V-spring PTFE-filled/V-spring	200/400	2
	PS20	NBR/POM	700	0,5
	PS23	PU/NBR/POM	400	0,5
	PS35	PU	400	0,4
	PS35A	PU	400	0,4

