






Back-up ringar

LAMISA

TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

*För högre temperaturer rekommenderar vi aluminium/stål.








PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	BUR08	POM, PTFE	-	-
	BUR09	POM, PTFE	-	-
	BUR10	POM, PTFE	-	-
	BUR11	POM, PTFE	-	-
	BUR12	POM, PTFE	-	-
	BUR13	POM, PTFE	-	-



TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	BWR01	POM, PTFE, Polyester-fabric	-	4
	BWR01A	POM, PTFE	-	4
	BWR03	POM, PTFE	-	4
	BWR04	POM, PTFE	-	4
	BWR05	POM, PTFE	-	4
	BWR06	POM, PTFE	-	4
	BWR07	POM, PTFE	-	4
	BWR08	POM, PTFE	-	4
	BWR09	-	-	-

