

Stångtätningar



TEMPERATURRESISTENS (°C)

PU (U500)	-30 till 125
NBR	-25 till 100
POM	-50 till 100*
PU-D57	-30 till 125
PTFE	-200 till 260

*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	RS01	PU, NBR, FPM	400/160/160	0,5
	RS01A	PU, NBR, FPM	300/160/160	0,5
	RS01B	PU, NBR, FPM	400/160/160	0,5
	RS01C	NBR, FPM	160/160	1
	RS02	PU/POM, NBR/POM, FPM/PTFE	700/250/250	0,5
	RS02A	PU/POM, NBR/POM, FPM/PTFE	700/250/250	0,5
	RS02B	PU/PTFE	700	0,5
	RS02C	PU/POM	400	5
	RS03	PU/NBR	400	0,5
	RS04	PU/NMB/POM	700	0,5
	RS04A	PU/NBR/POM	700	0,5
	RS05	PU, NBR	25	1
	RS05A	PU, NBR	25	1
	RS08	PU, NBR	400/160	0,3
	RS09	PU-D57/NBR, PTFE/NBR	600/400	5/10
	RS09A	PU-D57/NBR, PTFE/NBR	600/400	5/10
	RS09B	PU-D57/NBR, PTFE/NBR	600/400	5/10
	RS10-12B	PU/POM, NBR/POM	500/250	0,7
	RS91	PU-D57/NBR, PTFE/NBR	600/400	5/10
	RS91B	PU-D57/NBR, PTFE/NBR	600/400	5/10















Stångtätningar



TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	RS17	PU, NBR	400/160	0,5
	RS17A	PU/POM	700	0,5
	RS17B	PU/NBR	400	0,5
	RS17C	PU/NBR/POM	700	1
	RS17D	PU, NBR	400/160	0,5
	RS17E	PU/POM	700	0,5
	RS19	PTFE-virgin/V-spring PTFE-filled/V-spring	200 400	0,5
	RS19A	PTFE/V-spring	150	5
	RS20	NBR/POM	700	0,5
	RS31-33	PU/POM	500	0,5
	RS35	PU	400	0,5
	RS35A	PU	400	1

