













Svarvade Radialtätningar

LAMISA

TEMPERATURRESISTENS (°C)

PU (U500)	-30 till 125
NBR	-25 till 100
POM	-50 till 100*
PU-D57	-30 till 125
PTFE	-200 till 260

*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	OS01A	PU/POM, NBR/POM, FPM/PTFE	0,5, 0,5, 0,5	5, 10, 15
	OS02A	PU/POM, NBR/POM, FPM/PTFE	0,5, 0,5, 0,5	5, 10, 15
	OS03A	PU, NBR, FPM	0,5, 0,5, 0,5	5, 10, 15
	OS08	PU, NBR	-	5, 10
	OS08A	PU, NBR	-	5, 10
	R03	PU/POM, NBR/POM	400, 250	0,2, 0,2
	R04	PU, NBR	160, 100	0,2, 0,2
	R04A	PU, NBR	160, 100	0,2, 0,2
	R05	PU, NBR	160, 100	0,2, 0,2
	R05A	PU, NBR	160, 100	0,2, 0,2
	VR06	NBR	-	25
	VR07	NBR	-	25

