




















Symmetriska Tätningar

TEMPERATURRESISTENS (°C)

PU	-30 till 105
NBR	-25 till 100
POM	-50 till 80*
PU-D57	-30 till 105
PTFE	-25 till 100

*För högre temperaturer rekommenderar vi aluminium/stål.

PROFIL	TYP	STANDARDMATERIAL	TRYCK (Bar)	YTHASTIGHET (m/sek)
	PRS06	PU, NBR	400/160	0,5
	PRS06A	PU, NBR	300/160	0,5
	PRS06B	PU, NBR	400/160	0,5
	PRS06C	PU, NBR	400/160	0,3
	PRS06D	PU, NBR	400/160	0,5
	PRS06E	PU, NBR	400/160	0,5
	PRS07	PU/NBR	400	0,5
	PRS10SP	PU, FPM, POM	-	-
	PRS10-12	PU/POM, NBR/POM	500/250	0,5
	PRS10-12A	PU/POM, NBR/POM	500/250	0,7
	PRS13-15	PU/POM, NBR/POM	500/250	0,5
	PRS18	PU/NBR	400	0,5
	PRS19	PTFE-virgin/V-spring PTFE-filled/V-spring	200/400	15
	PRS19B	PTFE-virgin/Helicoil spring PTFE-filled/Helicoil spring	200/400	5
	PRS19C	PTFE-virgin/Helicoil spring PTFE-filled/Helicoil spring	200/400	5
	PRS19D	PTFE-virgin/Helicoil spring PTFE-filled/Helicoil spring	200/400	5
	PRS22	PU/POM, NBR/POM, FPM/PTFE	400/160/160	0,5
	PRS25-27	PTFE-virgin PTFE-filled	100	1,5
	PRS99	PU, NBR, FPM	400/160/160	0,5

